

Material Safety Data Sheet Purple Thunder

Section 1. Chemical Product and Company Identification

Product Name Purple Thunder

Product Number NTAL PTH

Manufacturer/ NuTech Specialties, Inc.
Supplier 9811 So. 6150 W.
West Jordan, UT 84088

Phone Number (801) 253-1000 (Mon-Fri/ 8am- 5pm MT)

D.O.T. Emergency

Phone:

1-800-633-8253

Date of September 25, 2012 **Revision Number** 1.0

Preparation

Section 2. Hazards Identification

Emergency overview This product is a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

DANGER!

Keep out of reach of children.

Keep container closed during storage. Ensure that eyewash stations and safety showers are proximal to the workstation location. S24/25- Avoid contact with skin and eyes.

Potential Acute Health

Effects

May cause eye irritation, de-fatting of the skin

Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by

coughing, choking, or shortness of breath.

Routes of Entry Ingestion, eye contact.

Eyes Eye Irritation

Skin De-fatting of the skin

Inhalation Causes no adverse effects

Ingestion May cause gastrointestinal irritation

Medical conditions aggravated by exposure:

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: lung (of example, asthma-like conditions), liver, and kidney.

Potential Chronic Health None

Carcinogenic Effects Not classified or listed by IARC, NTP, OSHA, EU and ACGIH.

Target Organs Acute lethal exposure to ethylene glycol monobutyl either in animal studies has resulted in

congestion of organs including kidney, spleen, and lung. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: mild, reversible liver effects, mild, reversible kidney effects, blood abnormalities.

Environmental Not available

Effects

Section 3. Composition and Info	rmation on Ingredients
---------------------------------	------------------------

Name	CAS#	% by Weight	Exposure Limits	LC50/LD 50
SOLVENT-BUTYL CELLOSOLVE	111-76-2	>15	25	25
CAUSTIC SODA-LIGUID	1310-73-2	>5	2MG/M3	2MG/M3
SODIUM METASILICATE	6834-92-0	>4	NONE	NONE
ALKANOLAMINE	141-43-5	>2		

Section 4. First Aid Measures

Eye Contact May cause eye irritation, flush eyes with running water for at least 15 minutes, keeping eyelids

open.

Skin Contact Wash gently and thoroughly the contaminated skin with running water and vinegar.

Inhalation

Ingestion Drink large volumes of water, then a solution of water and vinegar or other mildly acid fruit

juice. DO NOT INDUCE VOMITING

General Advice In case of Accident or if you feel unwell, seek medical advice immediately (show label or

MSDS where possible).

Notes to Physician Not available

Section 5. Fire Fighting Measures

Flammability No specific information is available in our database regarding the flammability of this product

is presence of various materials.

Fire Fighting Media and instructions

Not available

Products of Combustion Not available

Special Remarks on Fire

Hazards

Not available

Special Remarks on Explosion Hazards Not available

Sensitivity to Mechanical Impact

Not available

Sensitivity to Static Discharge

Not available

Protection of Fire Fighters See special remarks on Fire Hazards

Section 6. Accidental Release Measures

Personal Precautions Face shield. Full suit. Boots. Gloves. Suggested protective clothing might not be sufficient;

consult a specialist BEFORE handling this product.

Methods for Containment Absorb with an in inert material and put the spilled material in an appropriate waste disposal.

Environmental Consult local authorities for approved method of container disposal. Read label instructions **Precautions** carefully before using.

Methods for Clean Up See Methods for Containment

Section 7. Handling and Storage

Precautions Avoid contact with skin and eyes. After handling, always wash hands thoroughly with soap

and water.

Incompatibility Strong acids

Storage Corrosive materials should be stored in a separate safety storage cabinet or room. Keep out of

reach of children. For Institutional and Commercial Use.

Keep out of reach of children.

Keep container closed during storage. Ensure that eyewash stations and safety showers are proximal to the work station location. S24/25- Avoid contact with skin and eyes.

Section 8. Exposure Controls/Personal Protection

Engineering Controls

Personal Protection Adequate general ventilation should be sufficient to control airborne levels.

Eyes Splash goggles

Body Additional body garments should be used based upon the task being performed (e.g.,

sleevelets, apron, gauntlets, disposable suits) to avoid exposed skin surfaces.

Respiratory Not requited

Hands Rubber gloves

Protective Clothing (Pictograms)

Apron



Exposure Limits Sodium Hydroxide

TWA: $2 (mg/m^3)$ from OSHA (PEL)

Consult local authorities for acceptable exposure limits.

Section 9. Physical and Chemical Properties

Physical State and

Appearance

Purple liquid

Molecular Weight N/A

pH 13

Boiling/Condensation

Point

200F

Melting/Freezing Point <32 F

Critical Temperature N/A

Instability Temperature >212 F

Specific Gravity (H2O = 1): 1.077

Vapor Pressure (Non-Aerosols)(mm Hg and Temperature)

Vapor Density (Air = 1)

Solubility in Water Complete in water

VOC N/A

Evaporation Rate (H2O = 1) 0.85

Dispersion Properties N/A

Solubility Complete in water

The Product is: Alkaline Liquid

Auto-ignition

Temperature

N/A

Flash Points None below 212 F

Flammable Limits None below 212 F

Fire Hazards in Presence

Of Various Substances

N/A

Explosion Hazards in N/A Presence of Various Substances

Odor slight sassafras odor

Color Purple

Section 10. Stability and Reactivity Data

Stability The product is stable.

Incompatibility with Various Substance

Product will be neutralized if contacted by acid products

Hazardous Decomposition

Products

Not available

Section 11. Toxicological Information

Routes of Entry Ingestion, and eye contact.

Toxicity to Animals Per oral (Glycol Ether EB) {Rat} LD-50 (470-3000) MG/K9

Acute Effects on Humans Acute oral toxicity (LD50): 140 mg/kg {Rat}. (Sodium Hydroxide)

Eyes Eye Irritation

Skin De-fatting of the skin.

Inhalation Causes no adverse effects

Ingestion May cause gastrointestinal irritation

Chronic Effects on

Humans

Not classified or listed by IARC, NTP, OSHA, EU and ACGIH.

Special Remarks on Toxicity to Animals

No additional remark

Special Remarks on Chronic Effects on

Humans

No additional remark

Section 12. Ecological Information

Ecotoxicity Not available

BOD5 and COD Not available

Products of Possibly hazardous short term degradation products are not likely. However, long term

Biodegradation degradation products may arise.

Toxicity of the Products of

Biodegradation

Not available

Special Remarks on the

Products of Biodegradation

Not available

Section 13. Disposal Considerations

Waste Information If spilled, contain spill and dilute with clean water, wash all surfaces with clean water. For

disposal, dilute with large volumes of water and flush to sewer.

Waste Stream Not available

Section 14. Transport Information

DOT (U.S.A.) (Pictograms)

None

TDG Classification This product is not regulated by DOT when shipped

PIN UN, Proper Shipping

Name, PG

Shipping Name: Domestically by land.

Maritime Transportation None

Special Provisions for

Transport

Not available

Section 15. Regulatory Information and Pictograms

Regulatory Lists No products were found.

Other Regulations OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Other Classifications HCS (U.S.A.) HCS Class: Corrosive Liquid. HCS Class: Toxic.

USA Regulatory

Lists

This product does NOT contain components that are known to the state of California to Cause Cancer or Reproductive Harm at or above California

Prop 65 No Observable Effect Level (NOEL)

SARA 302 Extremely Hazardous Substances - Not listed

SARA 311 - 1. Immediate (acute) health hazard 2. Delayed (chronic) health hazard

SARA 313 Toxic Chemical List - Not listed

DSD (EEC)

R22- Harmful if swallowed. R35- Causes severe burns.

International

No Products were found.

Regulations Lists

Hazardous Material **Information System** U.S.A.)



National Fire Protection Association (U.S.A.)



WHMIS (Classification)

WHMIS CLASS E: Corrosive Liquid. WHMIS CLASS D-1: Material causing immediate and serious toxic effects.

The Hazard Ranking systems presented on this MSDS sheet provide only a quick reference for hazard information. The ENTIRE MSDS must be consulted to determine any specific hazards, First Aid measures, and PPE associated with this product.

Section 16. Other Information

Expiry Date 3 (Three Years) from the date of preparation indicated in Section 1

Validated by Verified by

Printed

Information Contact

Notice to Reader:

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.
Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution.

Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Validated on

NuTech Specialties, Inc.